

(12) UK Patent Application

(19) GB

(11) 2 223 476 (13) A

(43) Date of A publication 11.04.1990

(21) Application No 8819429.5

(22) Date of filing 16.08.1988

(71) Applicant

David J Instance Limited

(Incorporated in the United Kingdom)

Maldstone Road, Paddock Wood, Tonbridge, Kent,
TN12 6DF, United Kingdom

(72) Inventor

David John Instance

(74) Agent and/or Address for Service

Page White & Farrer

54 Doughty Street, London, WC1 2LS,
United Kingdom

(51) INT CL'

G09F 3/02 3/10

(52) UK CL (Edition J)

B8F FBF FBG

(56) Documents cited

GB 2197293 A GB 2191463 A

(58) Field of search

UK CL (Edition J) B8F FBF FBG

INT CL' G09F

(54) Labels and manufacture thereof

(57) A label for attachment to a container comprises a longitudinal strip 3 which is divided into a series of at least three panels 4, 6, 8 by at least two transverse fold lines 10, 12, the strip being folded about the transverse fold lines such that one panel 6 forms a front cover for the label and adjacent second and third panels at opposing ends of the front cover are folded about respective transverse fold lines behind the front cover and both form a rear surface of the folded longitudinal strip. A support piece 16, to which the rear surface of the folded longitudinal strip is attached by adhesive 19, is coated with a release material whereby the rear surface of the longitudinal strip is releasably adhered to the release material such that at least one of the first and second panels can be detached from the support piece to open the label.




Fig. 1.

1/1




Fig. 1.




Fig. 2.

"LABELS AND MANUFACTURE THEREOF".

The present invention relates to a label, and in particular, to a folded label to be attached to a container such as a bottle, can, packet or the like. The present invention also relates to a method of producing labels.

A known folded label is described in my U.K. Publication No. 2191463. That application discloses a label for attachment to a container, the label comprising a longitudinal strip which is divided into a series of panels by a plurality of transverse fold lines, the strip being folded about the transverse fold lines so that one end of the panel and the adjacent panel form rear and front cover panels, respectively, which envelope the remaining panel or panels of the folded strip, the rear cover panel of the strip being shorter in the longitudinal direction than at least the front cover panel and a third panel, which is adjacent to the front panel, extending beyond the free end of the rear cover panel and having a rearwardly directed overlapping portion; and a support web to which is adhered the rear surface of the rear cover panel, the overlapping portion being releasably adhered to the support web so as to maintain the folded label in a closed configuration, the arrangement being such that the label can be opened by detaching the overlapping portion from the support web. Such a label described in that application suffers from the disadvantage that the requirement for an overlapping portion limits the size of the inside panels of the label. Also, the support web needs to be larger than the rear cover panel to allow the flap to be adhered thereto. U.K. 2191463 also discloses that a layer of release material may be applied to the overlapping portion of the folded longitudinal strip, so as to improve the effectiveness with which the label can be repeatedly resealed. This makes the manufacture of a length of release backing material carrying a

succession of folded labels unnecessarily complicated since the release material must be applied in discrete steps.

It is an aim of the present invention to provide a label which makes effective use of the area of the longitudinal strip.

Accordingly the present invention provides a label for attachment to a container, the label comprising a longitudinal strip which is divided into a series of at least three panels by at least two transverse fold lines, the strip being folded about the transverse fold lines such that one panel forms a front cover of the label and adjacent second and third panels at opposing ends of the front cover are folded about respective transverse fold lines behind the front cover and both form a rear surface of the folded longitudinal strip; and a support piece to which the rear surface of the folded longitudinal strip is attached, the support piece being coated with a release material whereby the rear surface of the longitudinal strip is releasably adhered to the release material such that at least one of the first and second panels can be detached from the support piece to open the label.

The present invention also provides a method of producing a succession of labels carried on a length of release backing material, the method comprising the steps of:-

- a) providing a length of a laminar web comprising a self-adhesive support web, which is releasably adhered to a length of a release backing material;
- b) coating a front surface of the support web with a release material;
- c) adhering a succession of folded longitudinal strips to the coated front surface, each longitudinal strip being divided into a series of at least three panels by at least two transverse fold lines, the strip being folded about the transverse fold lines such that one

panel forms a front cover of the label and adjacent second and third panels at opposing ends of the front cover are folded about respective transverse fold lines behind the front cover and both form a rear surface of the folded longitudinal strip, the rear surface of each strip being adhered to the coated front surface; and

d) cutting a succession of support pieces from the support web thereby to form a succession of cut out labels carried on the release backing material, each cut out label including a respective folded longitudinal strip.

An embodiment of the present invention will now be described by way of example only with reference to the accompanying drawings in which:

Figure 1 is a perspective view of a folded label according to the present invention when carried on a length of release backing material; and

Figure 2 is a perspective view of the folded label of Figure 1 in a partially opened configuration.

Referring to Figure 1, a label 2 comprises a longitudinal sheet 3 e.g. of paper which is folded into a series of three panels 4, 6, 8 by a pair of transverse fold lines 10, 12. A middle panel 6 forms a front cover of the label 2, and second and third panels 4, 8 are at opposing ends of the front cover panel 6. The second panel 4 and the front cover panel 6 have substantially the same length in the longitudinal direction and are longer than the third panel 8. The second panel 4 is folded about the transverse fold line 10 between the second panel 4 and the front cover panel 6 so as to lie underneath the front cover panel 6, and the third panel 8 is folded about the other transverse fold line 12 between the front cover panel 6 and the third panel 8 so as to lie under the second panel 4. A portion 14 of the

second panel 4 overlaps the third panel 8. Further panels (not shown) can be attached to the free end of the second panel 4 and folded between the second panel and the front cover panel 6. These further panels can also have substantially the same dimensions as the front cover panel. A support piece 16 has a front surface 17 coated with a release material 18. Typically the support piece 16 is of clear plastics, preferably acetate. Typically the release material 18 comprises a mixture of polysiloxane and a varnish. Preferably, the mixture contains from 90 to 99.5 vol % polysiloxane such as a polysiloxane manufactured under the code name WS70M and WS78L by Wacker and sold in Great Britain by Ambersil Limited, Basingstoke, Hampshire as silicone fluid F100, and from 0.5 to 10 vol % varnish, such as an overprinting varnish made by Fishburn and having the code name XF 05546. The rear surface of the strip 2 comprises the rearwardly directed surface 20 of the third panel 8 and that part 22 of the rearwardly directed surface of the second panel 4 which is not covered by the third panel 8. The rear surface of the strip 2 is releasably adhered to the coated front surface of a respective support piece 16 by a pressure sensitive adhesive 19. The pressure sensitive adhesive 19 may be arranged in a continuous layer or in longitudinally directed strips. The support piece 16 is of the same width as the longitudinal strip 3 and extends beyond the transverse fold lines 10, 12 at the respective end of the folded longitudinal strip 3. The rear surface of the support piece 16 is self-adhesive and is releasably adhered to a release backing material 26, such as waxed paper. The support piece 16 may be adhered by the self-adhesive surface to a product to be labelled. Some or all of the surfaces of the strip 2 may be printed with e.g. textual information relating to the product to be labelled.

Referring to Figure 2, the label 2 may be opened by detaching the said rearwardly directed part 22 of the second panel 4 and the adhesive 19 adhered thereto from the release material 18, and

unfolding the label about the fold lines 10 and 12 so as to expose the previously hidden surfaces of the three panels 4, 6, 8. The label 2 can be completely removed from the support piece 16 by detaching the third panel 8 from the release material 18. The label 2 can also be reattached to the support piece 16 by replacing adhesive layer 19 on the third panel 8 against the release material 18, and resealed by folding the label 2 along fold lines 12 and 10 and replacing the adhesive layer 19 on the second panel 4 against the release material 18.

A succession of labels, the labels being labels as described above, may be releasably adhered to a strip of release backing material, so as to allow the labels to be adhered to respective containers by a continuous process.

A method for producing a succession of the labels of the present invention on a length of release backing material will now be described.

A length of a laminar web, which comprises a self-adhesive support web e.g. of plastic such as clear acetate, releasably adhered to a length of release backing material 26 e.g. coated paper is provided. The front surface of the self-adhesive support web is coated with a layer of release material 18 such as the polysiloxane varnish composition described above. A succession of longitudinal strips of paper 3 are each folded along two transverse fold lines 10, 12 to form three panels 4, 6, 8 as described above. The third panel 8 and the uncovered part of the second panel 4 of each folded longitudinal strip 3 are releasably adhered to the coated front surface of the self-adhesive support web by adhesive 19. Preferably the adhesive 19 is pressure sensitive adhesive. The release material 18 and self-adhesive support web are die cut parallel to, and beyond each end of each folded longitudinal strip 3 so as to form a support

piece 16 under each folded longitudinal strip 3, each support piece 16 being coated with release material 18. The edges of the laminar web and the longitudinal strips 3 are die cut to a required width. The unwanted strips of the self-adhesive support web formed between the support pieces 16 are then removed, together with the unwanted edge trimmings of the support web, so as to leave a succession of folded labels 2 carried on length of release backing material 26. The folded labels have the construction shown in Figure 1.

With the present invention, since the rear surface of the second panel is releasably adhered to the support piece, ~~the~~ overall dimensions of the second panel, and any remaining panels attached thereto, can be substantially the same as that of the front cover panel. This optimises the provision of labelling area. Also, the support piece can be substantially the same size as the majority of the panels in the label.

The preferred embodiments of the present invention can provide a folded label, the whole of one surface of which can be used to display information. Further, the folded label according to the present invention can have a total area which is not restricted by the area of the label which is adhered to the article carrying the labels.

The preferred embodiments of the present invention can further provide a method of producing a succession of folded labels carried on a length of release backing material which method is made simple by the application of a release material in a continuous layer.

CLAIMS.

1. A label for attachment to a container, the label comprising a longitudinal strip which is divided into a series of at least three panels by at least two transverse fold lines, the strip being folded about the transverse fold lines such that one panel forms a front cover for the label and adjacent second and third panels at opposing ends of the front cover are folded about respective transverse fold lines behind the front cover and both form a rear surface of the folded longitudinal strip; and a support piece to which the rear surface of the folded longitudinal strip is attached, the support piece being coated with a release material whereby the rear surface of the longitudinal strip is releasably adhered to the release material such that at least one of the first and second panels can be detached from the support piece to open the label.

2. A label according to claim 1 wherein the release material contains from 90 to 99.5 vol % polysiloxane and from 0.5 to 10 vol % varnish.

3. A label for attachment to a container substantially as hereinbefore described with reference to the accompanying drawings.

4. A length of release backing material carrying a succession of labels, the labels being as claimed in any foregoing claim.

5. A method of producing a succession of labels carried on a length of release backing material, the method comprising the steps of:-

a) providing a length of a laminar web comprising a self-adhesive support web, which is releasably adhered to a length of a release backing material;

b) coating a front surface of the support web with a release material;

c) adhering a succession of folded longitudinal strips to the coated front surface, each longitudinal strip being divided into a series of at least three panels by at least two transverse fold lines, the strip being folded about the transverse fold lines such that one panel forms a front cover of the label and adjacent second and third panels at opposing ends of the front cover are folded about respective transverse fold lines behind the front cover and both form a rear surface of the folded longitudinal strip; and

d) cutting a succession of support pieces from the support web thereby to form a succession of cut out labels carried on the release backing material, each cut out label including a respective folded longitudinal strip.

6. A method according to claim 5, wherein the release material contains from 90 to 99.5 vol % polysiloxane and from 0.5 to 10 vol % varnish.

7. A method of producing labels substantially as hereinbefore described with reference to the accompanying drawings.